

WIDE-FORMAT THERMAL IMAGESETTERS LIBERATOR™ XE

FILM UP TO 54 INCHES WIDE

**TRUE
1200 DPI
RESOLUTION**

**Direct Film Imaging
NO Darkroom
NO Processor
NO Chemicals**



**Ultimate Prepress Solution
for the Screen Printing,
Sign and Banner, POP and
Corrugated Industries**

A QUICK LOOK

- 18, 28.5, 36, 42 and 54" media widths
- 1200 dpi resolution
- Imaging of up to 6 inches per minute
- Closed Loop Registration (CLR) control
- Multi-Level Pulsing (MLP)
- Enhanced Nib Management (ENM)
- Harlequin RIP with media saving
- Chemistry, darkroom and processor-free
- NO inks, toners, cameras or disposal costs
- Automatic media cutter
- In-house production control
- Simple, hands-off operation
- Low maintenance



The high performance, 1200 dpi Liberator XE Wide-Format Thermal Imagesetters enable you to produce superb quality film separations right in your own shop—without a darkroom, without a processor and without chemicals. EXILE helps you to deliver those more demanding jobs efficiently while producing full-size film up to 54 inches wide. That is about 4 times bigger than other conventional products currently on the market.

EXILE's thermal imagesetter technology offers clear, compact, environmentally friendly solutions to artwork production, enabling you to eliminate outsourcing of large-format films and bring production control in-house. EXILE's unique, chemistry-free, dry-imaging ThermolImpression® film requires absolutely no fixers, developers, inks or toners while providing UV densities that exceed industry standards.

The Liberator XE Series is built using EXILE's innovative and proprietary technologies, including: Closed Loop Registration (CLR) control for accurate registration overlay, Multi-Level Pulsing (MLP) for superior dot quality, and Enhanced Nib Management (ENM) to provide smooth, high-quality images every time.

Liberator XE ThermolImpression Systems include a Harlequin® ScriptWorks® RIP Management System available on either a PC or Macintosh platform. This forward thinking, trouble-free fully featured RIP is PostScript compatible and is fully compliant with PostScript Language Level 3 specifications, the latest version of the PostScript page description language (PDL). Each system includes media saving functions and can be customized with trapping, proofing, and specialized screening to fit your requirements.

The bottom line: accurate registration, higher performance, versatility and flexibility.

WIDE-FORMAT THERMAL IMAGESETTERS LIBERATOR™ XE

FILM UP TO **54** INCHES WIDE

SPECIFICATIONS

Printhead Configuration	Single-substrate, linear array
Printing Method	Direct thermal technology
Resolution	600 x 600 or 1200 x 1200 dpi
Film Drive	Stepper motor
Paper Type	Thermolmpression™ Proofing Media
Paper Length	200 foot roll
Film Type	Thermolmpression™ Polyester Film
Film Length	200 foot roll
Optical Density (Film)	4.0 typical (UV)
Registration Accuracy	± 0.01 %*

*Measured at a length of 60 inches

OPERATING REQUIREMENTS

Voltage	115 or 230 VAC (Auto-switch)
Frequency	50-60 Hz
Power Usage	90 Watts idle mode 1,000 Watts plot/print mode
Temperature	Operating: 60° to 80° F (15° to 27° C) Storage/Shipping Range: 14° to 158° F (-10° to 70° C) Humidity: 5 to 95% non-condensing
Media Temperature	Operating: 60° to 80° F (15° to 27° C) Storage/Shipping Range: 14° to 86° F (-10° to 30° C) Humidity: 5 to 95% non-condensing



IMAGESETTER MODEL SELECTION CHART

Model	Liberator XE 1812	Liberator XE 2812	Liberator XE 3612	Liberator XE 4212	Liberator XE 5412
Media Width	18.25 in (46.35 cm)	28.5 in (72.4 cm)	36 in (91.44 cm)	42 in (106.68 cm)	54 in (137.16 cm)
Plot Width	17.92 in (45.52 cm)	28.16 in (71.53 cm)	35.84 in (91.04 cm)	41.81 in (106.20 cm)	53.76 in (136.55 cm)
Plot Rate	6.14 in/min	6.14 in/min	6.14 in/min	6.14 in/min	6.14 in/min
600 dpi	(15.6 cm/min)	(15.6 cm/min)	(15.6 cm/min)	(15.6 cm/min)	(15.6 cm/min)
Plot Rate	3.07 in/min	3.07 in/min	3.07 in/min	3.07 in/min	3.07 in/min
1200 dpi	(7.8 cm/min)	(7.8 cm/min)	(7.8 cm/min)	(7.8 cm/min)	(7.8 cm/min)
Height	11 in (27.9 cm)	11 in (27.9 cm)	11 in (27.9 cm)	11 in (27.9 cm)	11.25 in (28.6 cm)
Width	29 in (73.7 cm)	37.5 in (95.3 cm)	45 in (114 cm)	53 in (135 cm)	63 in (160 cm)
Depth	21 in (53.3 cm)	21 in (53.3 cm)	21 in (53.3 cm)	21 in (53.3 cm)	21 in (53.3 cm)
Net Weight	110 lb (50 kg)	130 lb (59 kg)	155 lb (70 kg)	185 lb (84 kg)	232 lb (105 kg)

Specifications are subject to change without notice.

LIMITED WARRANTY

EXILE Technologies warrants this product (excluding printhead) to be free from defects in material and workmanship for a period of one year from date of shipment. The thermal printhead is warranted for a period of three months from date of shipment.

Thermal printhead warranty may be extended to a full year with the execution of a film supply contract.



EXILE Technologies

7007 Pinemont Drive
Houston, Texas 77040 USA
713-343-5662 • 1-800-747-7651
Fax 713-986-8724
www.exiletech.com
sales@exiletech.com

EXILE Technologies Ltd

F3 Bramingham Business Park
Enterprise Way, Luton
Bedfordshire LU3 4BU England
44 (0) 1582 573980
Fax 44 (0) 1582 574945
sales@exiletech.co.uk